


PRODUCT SPECIFICATIONS

3015 BULLET ASSEMBLY. FOR SMALL CALIBER AMMUNITION.



3015 Bullet Assembly

TECHNICAL DATA

	MEASUREMENTS
Capacity (maximum) [tn.]	35.00
Stroke (maximum) [in.]	5.00
Shut height over bed [in.]	15.00
Speed [spm]	110.00
Clutch	Bliss #44 type "R"
Brake	Clamshell
Number of stations	15.00
Motor horsepower [hp]	7.50
Area of bed [in.]	F-B 11.00, L-R 43.00
Floor space-for legs [in.]	F-B 40.00, L-R 56.00
Floor space-for enclosure [in.]	F-B 83.00, L-R 120.00
Floor space-for enclosure [in.]	180.00 w/ side doors open
Height-includes enclosure [in.]	125.00 w/ optional 8.00 foot spacers
Weight-includes enclosure [lb.]	14,000.00
Control cabinet [in.]	Nema 12, 36 x 60 x18 floor standing
Electrical supply	220/240/380/440 three phase
Control voltage [VDC]	24.00
Compressed air requirements [psi]	70 @5.5cfm (3/4 NPT pipe inlet)
Lube oil supply [gal.]	1.50
Sound level [DBA]	Less than 85.00

CONTACT

Bliss Munitions Equipment

BCN Technical Services | 1004 East State Street

Hastings, Michigan 49058 | USA

Phone (269) 948-3300 | Fax (269) 984-3313

SALES / SERVICE (800) 642-5477

info@bcntechserv.com | www.bcntechserv.com