


## PRODUCT SPECIFICATIONS

# 5012 BULLET ASSEMBLY. FOR SMALL CALIBER AMMUNITION.



5012 Bullet Assembly

## TECHNICAL DATA

	MEASUREMENTS
Capacity (maximum) [tn.]	60.00
Stroke (maximum) [in.]	7.50
Shut height over bed [in.]	19.75
Speed [spm]	70.00
Clutch	Bliss #44 type "R"
Brake	Clamshell
Number of stations	12.00
Motor horsepower [hp]	10.00
Area of bed [in.]	F-B 13.00, L-R 52.00
Floor space-for legs [in.]	F-B 50.00, L-R 64.00
Floor space-for enclosure [in.]	F-B 90.00, L-R 130.00
Floor space-for enclosure [in.]	190.00 w/ side doors open
Height-includes enclosure [in.]	132.00 w/ optional 8.00 foot spacers
Weight-includes enclosure [lb.]	22,000.00
Control cabinet [in.]	Nema 12, 36 x 60 x18 floor standing
Electrical supply	220/240/380/440 three phase
Control voltage [VDC]	24.00
Compressed air requirements [psi]	70 @5.5cfm (3/4 NPT pipe inlet)
Lube oil supply [gal.]	1.50
Sound level [DBA]	Less than 85.00

## CONTACT

### Bliss Munitions Equipment

BCN Technical Services | 1004 East State Street

Hastings, Michigan 49058 | USA

Phone (269) 948-3300 | Fax (269) 984-3313

SALES / SERVICE (800) 642-5477

info@bcntechserv.com | www.bcntechserv.com